

XRT™ (Model 78086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

Bearings & Bushings

	Bearings & Bushings
5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)
5107A	Ball bearing, black rubber sealed (17x26x5mm) (2)
5196A	Ball bearing, black rubber sealed (20x32x7mm) (2)
5196X	Ball bearing, black rubber sealed, stainless (20x32x7mm) (2)
5120A	Ball bearings, black rubber sealed (12x18x4mm) (2)
5108A	Ball bearings, black rubber sealed (15x26x5mm) (2)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
	Body & Accessories
7005	
7825	Body mounts, front
7815	Body mounts, front & rear
7826	Body mounts, rear
7813	Body support (includes front mount & rear latch, roof & hood skid pads)/ 3x12mm CS (19) (attaches to #7812 body)
7812	Body, XRT [™] (clear, untrimmed, requires painting)/ window
/012	masks/ decal sheet
7812A	Body, XRT [™] , blue (painted, decals applied) (assembled with front &
10121	rear body supports for clipless mounting, roof & hood skid pads)
7812G	Body, XRT™, green (painted, decals applied) (assembled with front &
	rear body supports for clipless mounting, roof & hood skid pads)
7812T	Body, XRT [™] , orange (painted, decals applied) (assembled with front
	& rear body supports for clipless mounting, roof & hood skid pads)
7812X	Body, XRT™, ProGraphix® (graphics are printed, requires paint
	& final color application)/ decal sheet
7812R	Body, XRT™, red (painted, decals applied) (assembled with front &
	rear body supports for clipless mounting, roof & hood skid pads)
7899	Body, XRT™, Rock n' Roll (painted, decals applied) (assembled
	with front & rear body supports for clipless mounting, roof &
7000	hood skid pads)
7898	Body, XRT™, Solar Flare (painted, decals applied) (assembled with front & rear body supports for clipless mounting, roof &
	hood skid pads)
7823	Latch, body mount, front (for clipless body mounting)/ 3x12mm CS (6)
1020	(attaches to #7812 body)
7824	Latch, body mount, rear (for clipless body mounting)/ 3x12mm CS (4)
	(attaches to #7812 body)
7814	Skid pads (hood scoop)/ mount/ 3x12mm CS (11) (attaches to #7812
	body)
7816	Skid pads (roof)/ 3x12mm CS (8) (attaches to #7812 body)
	Bumpers & Skidplates
7834	Bumper mount, rear
7835	Bumper, front/ bumper mount, front
7837	Skid plate, center
7844	Skid plate, front (1), rear (1)/ rubber impact cushion (1)
	Chassis & Attachments
7022	
7833	Battery hold-down mounts, left (2)/ right (2)/ 4x15mm CCS (4)
7819 7825	Battery hold-down/ battery compartment spacers/ foam pads Body mounts, front
7815 7826	Body mounts, front & rear Body mounts, rear
7724	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15
1127	CS (4)
7834	Bumper mount, rear
7835	Bumper, front/ bumper mount, front
7822	Chassis
7723	Nerf bars, chassis (2)
7725	Seal kit, receiver box (includes o-ring, seals, and silicone grease)
7820	Servo mount/ bulkhead cover/ chassis brace/ steering cover /3x12mm
-	CS (2)
7837	Skid plate, center
7844	Skid plate, front (1), rear (1)/ rubber impact cushion (1)
7776	Wheelie bar, black (assembled)
7775	Wheels, wheelie bar (2)/ axles, wheelie bar (2)/ 10x15x4 plastic
	bushings (4) (for #7776 or 8976 wheelie bar)
7818	Wing mount
7818 7821	Wing mount Wing/ 4x12mm FCS (4)
	Wing mount
	Wing mount Wing/ 4x12mm FCS (4) CUSh Drive Components
7821	Wing mount Wing/ 4x12mm FCS (4) CUSh Drive Components Cush drive key/ pin/ elastomer damper
7821 7794	Wing mount Wing/ 4x12mm FCS (4) CUSh Drive Components
7821 7794 7793X	Wing mount Wing/ 4x12mm FCS (4) CIISh Drive Components Cush drive key/ pin/ elastomer damper Housing, cush drive (front & rear halves)

6440¥	
6449X 6449R	Spur gear, 54-tooth, steel (1.0 metric pitch, 20° pressure angle) Spur gear, 54-tooth, steel (wide face, 1.0 metric pitch)
	Differential Components
7781X	Carrier, differential (aluminum)/ 3x10mm CS (with threadlock) (4)/
	3x10mm FCS (with threadlock) (4) (requires #7783X spider gear shaft)
7781	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
5136X	Differential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights)
7880 7881	Differential, front, complete (fits X-Maxx® 8s or XRT™) Differential, rear, complete (fits X-Maxx® 8s or XRT™)
7782	Gear set, differential (output gears (2)/ spider gears (4)/16x23.5x.5
	TW(2))
5041	Grease, premium high performance (20cc)
7780 5040	Housing, differential (front/rear) Oil, differential (20M wt) (standard)
7790	Pinion gear, differential, 11-tooth (front) (heavy duty) (use with #7792
7704	35-tooth differential ring gear)
7791	Pinion gear, differential, 11-tooth (rear) (heavy duty) (use with #7792 35-tooth differential ring gear)
7792	Ring gear, differential, 35-tooth (heavy duty) (use with #7790, #7791 11-tooth differential pinion gears)
7783X	Spider gear shaft (2)/ spacers (4)/16x23.5x.5 stainless washer (2) (for
7783	#7781X aluminum differential carrier) Spider gear shaft (2)/ spacers (4)/16X23.5X.5 TW (2)
1103	
7054	Driveline Components
7851 7794	Bushings, driveshaft, front (1), rear (1) Cush drive key/ pin/ elastomer damper
7754X	Drive cup (1)/ 3x8mm CS (for use only with #7750X driveshaft)
7754R	Drive cup, steel, extreme heavy duty (2)/ 3x8mm CS, heavy duty
7755	(2) (use only with #7750X driveshaft) (machined, heat treated) Driveshaft assembly, center, aluminum
5040	Oil, differential (20M wt) (standard)
7751X	Rebuild kit, steel constant-velocity driveshaft (includes pins for 2
	driveshaft assemblies (for use only with #7750X driveshaft)
7836 7768A	Steering blocks, left & right Stub axle, aluminum (black-anodized) (1) (for use only with
TIOCA	#7750X driveshaft)
7768	Stub axle, aluminum (blue-anodized) (1) (for use only with #7750X driveshaft)
7768G	Stub axle, aluminum (green-anodized) (1) (for use only with #7750X driveshaft)
7768T	Stub axle, aluminum (orange-anodized) (1) (for use only with #7750X driveshaft)
7768R	Stub axle, aluminum (red-anodized) (1) (for use only with #7750X driveshaft)
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7758G 7758T	Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
7758R	Wheel nuts, splined, 17mm, servated (orange-anouzed) (4) Wheel nuts, splined, 17mm, servated (red-anodized) (4)
	Front Suspension & Steering
7726	Bulkhead tie bar, upper (1)/ lower (2) (steel)
7828	Bulkhead, front (lower)
7720	Bulkhead, front (upper)
7835	Bumper, front/ bumper mount, front
7832 7716	Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)
7847	Servo horn, steering/ linkage, steering (48mm, assembled with pivot
	balls)
7839	Shock tower, front (left & right halves)
7843	Steering bellcranks/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
7746X	Steering link, steel/ servo saver spring, heavy duty (use with #2085X metal gear servo)
7894	Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7893	Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7894X	Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7893X	Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7894G	Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7893G	Suspension arm, lower, green (1) (right, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit)

Page 2 XRT[™]: TQi[™] Traxxas Link[™] Enabled 2.4GHz Radio & TSM® (Model 78086-4) Parts List

Page 2	XRI'": IQI'" Iraxxas Link'" Enabled 2.4GHZ Radio
7894T	Suspension arm, lower, orange (1) (left, front or rear) (for use
	with #7895T X-Maxx® WideMaxx® suspension kit)
7893T	Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit)
7894R	Suspension arm, lower, red (1) (left, front or rear) (for use with
	#7895R X-Maxx® WideMaxx® suspension kit)
7893R	Suspension arm, lower, red (1) (right, front or rear) (for use with
7000	#7895R X-Maxx® WideMaxx® suspension kit) Suspension arms, upper, black (left or right, front or rear) (2) (for use
7892	with #7895 X-Maxx® WideMaxx® suspension kit)
7892X	Suspension arms, upper, blue (left or right, front or rear) (2) (for
	use with #7895X X-Maxx® WideMaxx® suspension kit)
7892G	Suspension arms, upper, green (left or right, front or rear) (2) (for
7892T	use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arms, upper, orange (left or right, front or rear) (2)
10021	(for use with #7895T X-Maxx® WideMaxx® suspension kit)
7892R	Suspension arms, upper, red (left or right, front or rear) (2) (for
77.40	use with #7895R X-Maxx® WideMaxx® suspension kit)
7743 7740	Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm
//40	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)
7742	Suspension pin set, shock mount (front or rear, hardened steel),
	4x25mm (2), 4x38mm (2)
7741	Suspension pins, 4x85mm (hardened steel) (2)
	Hardware
2584	3x12mm cap hex screws (6)
4859	CS 3x10 flathead (hex drive)
3474X	Dual cooling fan kit, low profile (with shroud) (fits #3491 motor)
4955 3234	Pins, axle (2.5x12mm) (4) Screws, 2.5x14mm cap-head machine (hex drive) (6)
2577	Screws, 3x10mm button-head machine (hex drive) (6)
2587	Screws, 3x10mm caphead machine (6) (no washer)
2551	Screws, 3x10mm countersunk machine (6) (hex drive)
2578	Screws, 3x12mm button-head machine (hex drive) (6)
2579	Screws, 3x15mm button-head machine (hex drive) (6)
2586 2581	Screws, 3x15mm cap-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6)
2575	Screws, 3x23mm button-head machine (hex drive) (6)
2576	Screws, 3x8mm button-head machine (hex drive) (6)
2535	Screws, 4x10mm countersunk machine (hex drive) (6)
3937	Screws, 4x12mm button-head machine (hex drive) (6)
3938	Screws, 4x14mm button-head machine (hex drive) (6)
2594 2546	Screws, 4x15mm button-head machine (hex drive) (6) Screws, 4x15mm countersunk machine (hex drive) (6)
3933	Screws, 4x16mm button-head machine (hex drive) (6)
2547	Screws, 4x18mm countersunk machine (hex drive) (6)
2589	Screws, 4x20mm button-head machine (hex drive) (6)
2597	Screws, 4x22mm button-head machine (hex drive) (6)
2596 2598X	Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x30mm button-head machine (hex drive) (6)
2595	Screws, 4x35mm button-head machine (hex drive) (6)
4897	Screws, set (grub) 4mm (6) (w/ threadlock)
2743	Set (grub) screws, 3mm hardened (12)
3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
5480X	Wheel wrench, splined, 17 mm
	LED Lights
7882	Extension harness, LED lights (high-voltage)
6590	High-Voltage Power Amplifier
7884	LED light bar, front (high-voltage) (40 white LEDs (double row), 82mm wide) (fits Maxx®, X-Maxx®, or XRT™)
7883	LED light bar, rear, red (with white reverse light) (high-voltage)
	(24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount (fits
	Maxx®, X-Maxx®, or XRT™)
7885	LED light kit,complete (includes #6590 high-voltage power amplifier)
	Motors & Electronics
77.40	
7749	Adapter, standard servo (adapts standard servo to fit in Maxx®, X-Maxx®, or XRT™)
3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
7787	Covers, gear (2)
3474X	Dual cooling fan kit, low profile (with shroud) (fits #3491 motor)
2087	Gear set (for 2085 servo)
2087X	Gear set, metal (for 2085, 2085X servos)
3362X 7760	Heat sink, low profile, Velineon® 1200XL Motor mounts (front and rear)/ pins (4)
3491	Motor, Velineon® 1200XL, brushless
3492	Rebuild kit, Velineon® 1200XL (includes plastic endbells (2),
	6x17x6mm ball bearings (2), 6x8x.3 washer (1), 6x8x1 washer (1),
2086	7x6x12 spacer (1)) Servo case/gaskets (for 2085 & 2085X servos)

2085	
	Servo, digital high-torque (ball bearing), waterproof
2085X	Servo, digital high-torque, metal gear (ball bearing), waterproof/
	servo saver spring/ steering link
3496	Velineon® VXL-8s Electronic Speed Control, waterproof (brushless)
7759	(fwd/rev/brake) Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm
1109	BCS (4)
7759G	Washers, motor mount, aluminum (green-anodized) (4)/ 4x18mm
	BCS (4)
7759R	Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm
	BCS (4)
	Radio System, Batteries & Chargers
2872X	5000mah 11.1v 3-Cell 25C LiPo Battery
2889X	5000mAh 14.8v 4-Cell 25C LiPo iD® Battery
2857X 2890X	6400mah 11.1v 3-Cell 25C LiPo Battery 6700mah 14.8v 4-Cell 25C LiPo Batterv
20307	AA 4PK
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
2943	Battery charge indicators, green (4), gray (4), blue (4)
6548	Battery door, TQ 2.4 transmitter (replacement for #6516, 6517, 6528,
	6529, 6530 transmitters)
2990	Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2))
2997	Battery/charger completer pack (includes #2973 Dual iD charger
	(1), #2890X 6700mAh 14.8V 4-cell 25C LiPo iD® Battery (2))
2972	Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery
	Identification
2973	Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification
2970	Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery
	Identification
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery
	Identification
2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto
6525	Battery Identification Communication link, telemetry expander
2087	Gear set (for 2085 servo)
2087X	Gear set, metal (for 2085, 2085X servos)
2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for
	Traxxas iD batteries)
2938X	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas iD batteries)
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for
	Traxxas iD batteries)
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)
6552	Seal kit, expander box (includes o-ring, seals, and silicone
6576	grease)
6526 6527	Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage
6531	
	Sensor, temperature & voltage (fits X-Maxx® or XRT™)
6521	Sensor, temperature & voltage (fits X-Maxx® or XRT™) Sensor, temperature and voltage (long)
6521 2086	
2086 2085	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof
2086	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/
2086 2085 2085X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
2086 2085 2085X 6553X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system
2086 2085 2085X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module)
2086 2085 2085X 6553X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with
2086 2085 2085X 6553X 6550X 6551X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)
2086 2085 2085X 6553X 6550X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link
2086 2085 2085X 6553X 6550X 6551X 6559R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)
2086 2085 2085X 6553X 6550X 6551X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link
2086 2085 2085X 6553X 6550X 6551X 6550R 6509R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQI 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQI 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)
2086 2085 2085X 6553X 6550X 6551X 6550R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-
2086 2085 2085X 6553X 6550X 6551X 6559R 6509R 6507R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry Expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only)
2086 2085 2085X 6553X 6550X 6551X 6550R 6509R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-
2086 2085 2085X 6553X 6550X 6551X 6559R 6509R 6507R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only)
2086 2085 2085X 6553X 6550X 6551X 6509R 6509R 6528 6528 6529 6530	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry Expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)
2086 2085 2085X 6553X 6550X 6551X 6509R 6509R 6507R 6528 6529	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry Expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)
2086 2085 2085X 6553X 6550X 6551X 6509R 6509R 6528 6528 6529 6530	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry Expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)
2086 2085 2085X 6553X 6550X 6551X 6509R 6509R 6528 6528 6529 6530	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry Expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only) Traxas Link Wireless Module <u>RCently-TO-Racce Motie</u> XRT™: Brushless Electric Race Truck with TQi™ Traxxas Link™
2086 2085 2085X 6553X 6550X 6550R 6509R 6509R 6528 6528 6529 6530 6511	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only) Traxas Link Wireless Module <u>Recently-To-Racce Motice</u> XRT™: Brushless Electric Race Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management
2086 2085 2085X 6553X 6550X 6550R 6509R 6509R 6528 6528 6529 6530 6511	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry Expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM© (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only) Traxsta Link Wireless Module Recetty - To - Race Mote XRT™: Brushless Electric Race Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®
2086 2085 2085X 6553X 6550X 6550R 6509R 6509R 6528 6529 6529 6530 6511 78086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only) Traxas Link Wireless Module <u>Recetify-TO-Racce Motice</u> XRT™: Brushless Electric Race Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)® <u>Recetify-Constant</u>
2086 2085 2085X 6553X 6550X 6550R 6509R 6507R 6528 6529 6530 6511 78086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry Expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6551X GPS module) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3- channel (transmitter only) Traxas Link Wireless Module <u>Recently-To-Racce Motice</u> XRT™: Brushless Electric Race Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)® <u>Bulkhead tie bar, upper (1)/ lower (2) (steel)</u>
2086 2085 2085X 6553X 6550X 6550R 6509R 6509R 6528 6529 6529 6530 6511 78086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, Candido System (for use only with #6550X telemetry expander 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only) Traxas Link Wireless Module <u>Recently-Co-Racce Montel</u> XRT [™] : Brushless Electric Race Truck with TQi [™] Traxxas Link [™] Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)® <u>Rear Suspension</u>

7716 Mount, tie bar, front (1)/ rear (1)

Page 3 XRT™: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 78086-4) Parts List

Page 3	
7838	Shock tower, rear (left & right halves)
7894	Suspension arm, lower, black (1) (left, front or rear) (for use with
7893	#7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with
7894X	#7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with
	#7895X X-Maxx® WideMaxx® suspension kit)
7893X	Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7894G	Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7893G	Suspension arm, lower, green (1) (right, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7894T	Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit)
7893T	Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit)
7894R	Suspension arm, lower, red (1) (left, front or rear) (for use with #7895R X-Maxx® WideMaxx® suspension kit)
7893R	Suspension arm, lower, red (1) (right, front or rear) (for use with #7895R X-Maxx® WideMaxx® suspension kit)
7892	Suspension arms, upper, black (left or right, front or rear) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7892X	Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7892G	Suspension arms, upper, green (left or right, front or rear) (2) (for use with #78956 X-Maxx® WideMaxx® suspension kit)
7892T	Suspension arms, upper, orange (left or right, front or rear) (2)
	(for use with #7895T X-Maxx® WideMaxx® suspension kit)
7892R	Suspension arms, upper, red (left or right, front or rear) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit)
7743	Suspension pin retainer (4)
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm
7742	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel),
7741	4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2)
7741	Shock Oil
5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
5033 5034	Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
5034	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
5029	Shock oil bottle (60cc) (for mixing shock oil)
5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack)
5038	Spinning carousel rack
	Shocks (GTX)
7866A	Body, GTX shock, medium (aluminum, black-anodized) (1)
7866	Body, GTX shock, medium (aluminum, blue-anodized) (1)
7866G	Body, GTX shock, medium (aluminum, green-anodized) (1)
7866T	Body, GTX shock, medium (aluminum, orange-anodized) (1)
7866R	Body, GTX shock, medium (aluminum, red-anodized) (1)
7866X	Body, GTX shock, medium (hard-anodized, PTFE-coated
7762	aluminum) (1) Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston
7764A	nuts, bladders) (renews 2 shocks) Shock caps, aluminum (blue-anodized), GTX shocks (2)/ spacers
7764G	(2) Shock caps, aluminum (green-anodized), GTX shocks (2)/
7764X	spacers (2) Shock caps, aluminum (hard-anodized, PTFE-coated), GTX
7764R	shocks (2)/ spacers (2) Shock caps, aluminum (red-anodized), GTX shocks (2)/ spacers
7764	(2) Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14 CS (2) (for
7863	2 shocks) Shock shaft, 92mm (GTX) (steel, chrome finish) (2) (assembled with
7863T	rod ends & hollow balls) Shock shaft, 92mm (GTX) (TiN-coated) (2) (assembled with rod
7861A	ends & hollow balls) Shocks, GTX, medium (aluminum, black-anodized) (fully
7861	assembled w/o springs) (2) Shocks, GTX, medium (aluminum, blue-anodized) (fully assembled
7861G	w/o springs) (2) Shocks, GTX, medium (aluminum, green-anodized) (fully assembled
	w/o springs) (2)
7861T	Shocks, GTX, medium (aluminum, orange-anodized) (fully assembled w/o springs) (2)

	, , , , , , , , , , , , , , , , , , ,
7861R	Shocks, GTX, medium (aluminum, red-anodized) (fully assembled
7767	w/o springs) (2) Spring retainer (adjuster), blue-anodized aluminum, GTX shocks
7767G	(4) (assembled with o-ring) Spring retainer (adjuster), green-anodized aluminum, GTX
11010	shocks (4) (assembled with o-ring)
7767X	Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks (4) (assembled with o-ring)
7767R	Spring retainer (adjuster), red-anodized aluminum, GTX shocks (4) (assembled with o-ring)
7845	Springs, shock, medium (natural finish) (GTX) (2.355 rate) (2)
7841	Springs, shock, medium (natural finish) (GTX) (2.599 rate, white stripe) (2)
7865	Springs, shock, medium (natural finish) (GTX) (2.899 rate, orange stripe) (2)
7864	Springs, shock, medium (natural finish) (GTX) (3.141 rate, green stripe) (2)
7859	Springs, shock, medium (natural finish) (GTX) (3.445 rate, tan stripe) (2)
7849	Springs, shock, medium (natural finish) (GTX) (3.744 rate) (2)
7842	Springs, shock, medium (natural finish) (GTX) (4.101 rate, pink stripe) (2)
7848	Springs, shock, medium (natural finish) (GTX) (4.594 rate, blue stripe) (2)
7850	Springs, shock, medium (natural finish) (GTX) (5.059 rate, red stripe) (2)
7846	Springs, shock, medium (natural finish) (GTX) (5.543 rate, yellow
	stripe) (2)
C 40 4 X	Spur Gears & Pinion Gears
6484X	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6485X 6486X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6488X	Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6491X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6480X	Gear, 19-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6494X	Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6493X	Gear, 21-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6405V	(for use only with steel spur gears)
6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6481X	Gear, 23-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6492X	Gear, 25-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
- ·	(for use only with steel spur gears)
6497	Gear, 26-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6447R	Spur gear, 46-tooth, steel (wide face, 1.0 metric pitch)
6448R 6449X	Spur gear, 50-tooth, steel (wide face, 1.0 metric pitch) Spur gear, 54-tooth, steel (1.0 metric pitch, 20° pressure angle)
6449A 6449R	Spur gear, 54-tooth, steel (vide face, 1.0 metric pitch)
04431	
	Steering Components
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
7847	Servo horn, steering/ linkage, steering (48mm, assembled with pivot balls)
7843	Steering bellcranks/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
7746X	Steering link, steel/ servo saver spring, heavy duty (use with
7897	#2085X metal gear servo) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use
79074	with #7895 X-Maxx® WideMaxx® suspension kit)
7897A	Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMeyr® currencion tit)
7897X	WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum,
1031X	stronger than titanium) (2) (for use with #7895X X-Maxx®
	WideMaxx® suspension kit)
7897G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum,
	stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7897R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum,
	Stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit)
	Suspension Linkage
	-
7798	Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542B, 8542T, 8542V) (includes (1) loft and (1)
	7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)

Page 4 XRT™: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 78086-4) Parts List

Page 4	XRT™: TQi™ Traxxas Link™ Enabled 2.4GHz Radio
7797	Rod ends (4) (assembled with steel pivot balls) (replacement
	ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
7743 7740	Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm
1140	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)
7742	Suspension pin set, shock mount (front or rear, hardened steel),
7744	4x25mm (2), 4x38mm (2)
7741 7897	Suspension pins, 4x85mm (hardened steel) (2) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use
	with #7895 X-Maxx® WideMaxx® suspension kit)
7897A	Toe links, front (TUBES black-anodized, 7075-T6 aluminum,
	stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum,
	stronger than titanium) (2) (for use with #7895X X-Maxx®
7897G	WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum,
	stronger than titanium) (2) (for use with #7895G X-Maxx®
70070	WideMaxx® suspension kit)
7897R	Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx®
	WideMaxx® suspension kit)
	Team Traxxas Items
2514	Decal sheet, racing sponsors
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)
9909	Traxxas® racing banner, red & black (3x7 feet)
	Tires & Wheels
7772A	Tires & wheels, assembled, glued (X-Maxx® black chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7774A	Tires & wheels, assembled, glued (X-Maxx® black chrome
	wheels, Sledgehammer® tires, foam inserts) (left & right) (2)
7877	Tires & wheels, assembled, glued (X-Maxx® black wheels, Gravix™ tires, foam inserts) (left & right)
7772X	Tires & wheels, assembled, glued (X-Maxx® black wheels,
	Maxx® AT tires, foam inserts) (left & right) (2)
7773	Tires & wheels, assembled, glued (X-Maxx® black wheels, paddle tires, foam inserts) (left & right) (2)
7772G	Tires & wheels, assembled, glued (X-Maxx® green wheels,
	Maxx® AT tires, foam inserts) (left & right) (2)
7774G	Tires & wheels, assembled, glued (X-Maxx® green wheels, Sledgehammer® tires, foam inserts) (left & right) (2)
7772T	Tires & wheels, assembled, glued (X-Maxx® orange wheels,
	Maxx® AT tires, foam inserts) (left & right) (2)
7774T	Tires & wheels, assembled, glued (X-Maxx® orange wheels, Sledgehammer® tires, foam inserts) (left & right) (2)
7772R	Tires & wheels, assembled, glued (X-Maxx® satin chrome
	wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7872	Tires & wheels, assembled, glued (XRT™ Race black wheels, Gravix™ tires, foam inserts) (left & right)
7875	Tires & wheels, assembled, glued (XRT™ Race black wheels,
	Maxx® AT tires, foam inserts) (left & right)
7876	Tires & wheels, assembled, glued (XRT™ Race black wheels, Sledgehammer® tires, foam inserts) (left & right)
7873	Tires, Gravix™ (left & right)/ foam inserts (2)
777 0X	Tires, Maxx® AT (left & right) (2)/ foam inserts (2)
7757	Wheel hex clips (6)
7756 7756X	Wheel hubs, hex (2)/ hex clips (2) Wheel hubs, hex, aluminum (blue-anodized) (4)
7756G	Wheel hubs, hex, aluminum (green-anodized) (4)
7756R	Wheel hubs, hex, aluminum (red-anodized) (4)
7758A 7758	Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (1)
7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
5480X 7771	Wheel wrench, splined, 17 mm Wheels, X-Maxx®, black (left & right)
7874	Wheels, XRT™ Race, black (left and right)
7796	Center drive, torque-biasing (assembled)/ 17x26x5 ball bearings (2)
7707	(requires #7727X bulkheads)
7787 7785X	Covers, gear (2) Input gear, transmission, 20-tooth/ 2.5x12mm pin
7786X	Input shaft, transmission (cush drive)
5040	Oil, differential (20M wt) (standard)
7784X	Output gear, 51-tooth, metal (requires #7785X input gear)
	Traxxas Tools
3433X 3433	Body reamer (aluminum handle) Body reamer (clastic bandle)
3433 3436	Body reamer (plastic handle) Cap, body reamer
	·····

3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
	premium handle (medium), travel pouch, hex drivers (straight:
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
8720	and 8.0mm), 1/4" drive
8720	Speed bit handle, large (overmolded) Speed bit handle, medium (one piece)
8722	Speed bit handle, medium (one piece) Speed bit handle, premium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
0/10	premium handle (medium), travel pouch, hex drivers (straight:
	1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,
	3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm,
	7.00mm, 8.00mm), 1/4" drive
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,
	includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
	2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
	handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Grive Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
0/10	3.0mm) 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
	2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
	2.5mm, 3.0mm), 1/4" drive
2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench /
	2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
••	3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut
	drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips,
	#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm
5480X	wrenches/ driver handle)
J400A	Wheel wrench, splined, 17 mm
	Turnbuckles & Threaded Rods
7798	Insert, threaded steel (replacement inserts for #7748G, 7748R,
	7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)
7797	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement
7797	right threaded insert)
7797 7897	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use
7897	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum,
7897	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx®
7897	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum,
7897 7897A	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx®
7897 7897A 7897X	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7897 7897A	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx®
7897 7897A 7897X	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx®
7897 7897A 7897X	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx®
7897 7897A 7897X 7897G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx®
7897 7897A 7897X 7897G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) WitteMaxx® Suspension kit) WitteMaxx® Suspension kit)
7897 7897A 7897X 7897G 7897R	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Do links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with
7897 7897A 7897X 7897G 7897R 7896 7894	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) ((left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895F X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895F X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895F X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896 7894	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896 7894 7893	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895F X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895F X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895F X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896 7894 7893	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896 7894 7893 7894X 7893X	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895K X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896 7894 7893 7894X	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Deriveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7897 7894 7893 7894X 7893X 7894G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Delinks , front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Delinks , front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Delinks , front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft , steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7896 7894 7893 7894X 7893X	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Deriveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897 7897A 7897X 7897G 7897R 7897 7894 7893 7894X 7893X 7894G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, gree
7897 7897A 7897A 7897G 7897G 7897R 7896 7894 7893 7894X 7893X 7894X 7893X 7894G 7893G 7894T	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, o
7897 7897A 7897X 7897G 7897G 7897R 7894 7894 7894 7894X 7894X 7894G 7893G	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (right, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower,
7897 7897A 7897A 7897G 7897G 7897R 7894 7893 7894 7893X 7894X 7894G 7894G 7894G 7894T 7893T	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (right, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower,
7897 7897A 7897A 7897G 7897G 7897R 7896 7894 7893 7894X 7893X 7894X 7893X 7894G 7893G 7894T	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, or
7897 7897A 7897A 7897G 7897G 7897R 7894 7893 7894 7893X 7894X 7894G 7894G 7894G 7894T 7893T	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (right, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (right, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower,
7897 7897A 7897A 7897G 7897G 7897R 7894 7894 7894 7894X 7894X 7894G 7893G 7894T 7893T 7894R	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, red (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, red (
7897 7897A 7897A 7897G 7897G 7897R 7894 7894 7894 7894X 7894X 7894G 7893G 7894T 7893T 7894R	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (right, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (right, front or rear) (for use with #78955X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (right, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, red (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, re
7897 7897A 7897A 7897G 7897G 7897R 7894 7894 7894 7893X 7894X 7893X 7894G 7893G 7894 7893 7894 7893 7894 7893 7894 7893 7894 7893 7894 7893 7894 7893 7893 7893 7893 7893 7893 7893 7893	right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit) Driveshaft, steel constant velocity (shaft only, 190.3mm) (1) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, black (1) (left, front or rear) (for use with #7895 X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, blue (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, green (1) (left, front or rear) (for use with #7895X X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895G X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, orange (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, red (1) (left, front or rear) (for use with #7895T X-Maxx® WideMaxx® suspension kit) Suspension arm, lower, red (

REV. 221027 1039

Page 5 XRT™: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 78086-4) Parts List

7892X	Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7892G	Suspension arms, upper, green (left or right, front or rear) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit)
7892T	Suspension arms, upper, orange (left or right, front or rear) (2) (for use with #7895T X-Maxx® WideMaxx® suspension kit)
7892R	Suspension arms, upper, red (left or right, front or rear) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit)
7895	Suspension kit, X-Maxx® WideMaxx®, black (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895X	Suspension kit, X-Maxx® WideMaxx®, blue (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895G	Suspension kit, X-Maxx® WideMaxx®, green (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895T	Suspension kit, X-Maxx® WideMaxx®, orange (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7895R	Suspension kit, X-Maxx® WideMaxx®, red (includes front & rear suspension arms, front toe links, driveshafts, shock springs)
7897	Toe links, 202.5mm (187.5mm center to center) (black) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897A	Toe links, front (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895 X-Maxx® WideMaxx® suspension kit)
7897X	Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895X X-Maxx® WideMaxx® suspension kit)
7897G	Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895G X-Maxx®

stronger than titanium) (2) (for use with #7895G X-Maxx® WideMaxx® suspension kit) 7897R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #7895R X-Maxx® WideMaxx® suspension kit)

If you have questions or need technical assistance, call Traxxas at:



(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com TRAXXAS.COM